

BABA Q10

Recessed optic downlights

design Jude Allen



A range of recessed luminaires that combines an extremely neat and minimalist design with a high degree of visual comfort: the extremely low edge and the recessed optic make it an innovative and effective element, ideal for applications ranging from the accentuation of display elements or architectural details to general lighting.

Un gamma di incassi che associa un design estremamente curato e minimale ad un elevato comfort visivo: il bordo estremamente ridotto e l'ottica arretrata ne fanno un elemento innovativo ed efficace, ideale per applicazioni che spaziano dall'accento di elementi espositivi o di dettagli architettonici all'illuminazione generale.

Une gamme de luminaires encastrés qui allie un design extrêmement soigné et minimaliste à un haut degré de confort visuel : le bord extrêmement bas et l'optique encastrée en font un élément innovant et efficace, idéal pour des applications allant de l'accentuation d'éléments de présentation ou de détails architecturaux à l'éclairage général.

Eine Reihe von Einbauleuchten, die ein extrem sauberes und minimalistisches Design mit einem hohen Maß an visuellem Komfort verbindet: die extrem niedrige Kante und die versenkte Optik machen sie zu einem innovativen und wirksamen Element, das sich ideal für Anwendungen eignet, die von der Akzentuierung von Ausstellungselementen oder architektonischen Details bis hin zur Allgemeinbeleuchtung reichen.

IP44 made in Italy



Supply current

500mA ($V_f 18V$)

Power

10W


Series wiring

CRI


85-93 (2700K-3000K-4000K only)

2-Step MacAdam


Dimensions



Photometric diagrams




CCT/CRI/Flux



Code construction

BAQ1 X X X X



Accessories

LBAQ101

Low luminance louver



SBAQ101

Milky screen



Note: The filter and the screen must be ordered together with the lighting fixture.

AL7022

24VDC/500mA constant current converter

Drivers 500mA

on/off

AL1074 (1) IP20 \varnothing 30 mm

AL1077 (1) IP20 \varnothing 40 mm

AL1084 (1..2) IP20 S.P. \varnothing 55 mm

dimnable

AL4010 (1..2) IP20 PUSH 0/1..10V \varnothing 72 mm

ALD450 (1) IP20 DALI 2 PUSH \varnothing 36 mm

AL4151 (1..2) IP20 DALI 2 \varnothing 72 mm

AL4153 (1..2) IP20 PUSH IGBT-TRIAC \varnothing 56 mm