

DIDDI

Trimless downlights

design Roberto Mantovani



Trimless downlight with extremely clean 3° light beam. The recessed optic makes it an innovative and effective element, able to offer effective lighting solutions.

Un apparecchio da incasso trimless di dimensioni compatte progettato per garantire un fascio luminoso di 3°, nel quale l'ottica arretrata ed un'emissione estremamente pulita consentono applicazioni precise ed efficaci.

Encastrable à plafond trimless avec un faisceau lumineux de 3° d'une propreté extrême. L'optique en retrait en fait un élément innovant et efficace, capable d'offrir des solutions lumineuses efficaces.

Randlose Deckenleuchte mit extrem reinem 3°-Lichtstrahl. Die eingelassene Optik macht es zu einem innovativen und effektiven Element, das in der Lage ist, effektive Beleuchtungslösungen anzubieten.

Downlight sin bordes con un haz de luz de 3° extremadamente limpio. La óptica empotrada lo convierte en un elemento innovador y eficaz, capaz de ofrecer soluciones de iluminación eficaces.



IP44 made in Italy

Supply current
350-500mA (V, 2.9V)


Power
1-2W

Series wiring


CRI
85

2-Step MacAdam

Dimensions



Photometric diagrams




CCT/CRI/Flux

| | 350mA | 500mA |
|-------|-------|-------|
| 2700K | 89lm | 128lm |
| 3000K | 93lm | 133lm |
| 4200K | 103lm | 154lm |


Code construction

DID X X 3



Accessories

ZTC10U ZTC10UB
White Black
Plasterboard recessing frame



LDID01
Low luminance louver



Note: The filter must be ordered together with the lighting fixture.

Drivers 350mA

on/off
AL1034 (1..11) IP20 ⌀ 30 mm
AL1035 (1..11) IP20 ⌀ 40 mm
AL1037 (1..16) IP20 S.P. ⌀ 55 mm
 dimmable
AL4000 (1..12) IP20 PUSH 0/1..10V ⌀ 72 mm
ALD435 (1..11) IP20 DALI 2 PUSH ⌀ 36 mm
AL4051 (2..14) IP20 DALI 2 ⌀ 72 mm
AL4053 (1..14) IP20 PUSH IGBT-TRIAC ⌀ 56 mm

Drivers 500mA

on/off
AL1074 (1..7) IP20 ⌀ 30 mm
AL1077 (1..6) IP20 ⌀ 40 mm
AL1084 (1..11) IP20 S.P. ⌀ 55 mm
 dimmable
AL4010 (1..12) IP20 PUSH 0/1..10V ⌀ 72 mm
ALD450 (1..7) IP20 DALI 2 PUSH ⌀ 36 mm
AL4151 (2..14) IP20 DALI 2 ⌀ 72 mm
AL4153 (1..14) IP20 PUSH IGBT-TRIAC ⌀ 56 mm

AL7022
24VDC/500mA constant current converter