

JOS PT2

Trimless pendants

design Roberto Mantovani



A suspended adjustable projector for trimless recessed installation, characterized by a minimal design and high optical performance. It lends itself to accent lighting applications, giving the chance to combine various color temperatures and beam angles, with CRI85.

Proiettore sospeso orientabile per installazione ad incasso trimless, connotato da un design minimale ed elevate prestazioni ottiche, si presta ad applicazioni di luce d'accento. Offre la possibilità di combinare temperature colore ed aperture di fascio, con CRI85.

Projecteur suspendu pour installation encastrée trimless, caractérisé par un design minimal et des performances optiques élevées. Il se prête aux applications d'éclairage d'accentuation, offrant la possibilité de combiner différentes températures de couleur et angles de faisceau, avec CRI85.

Abgehängter Projektor Projektor für den randlosen Einbau, der sich durch ein minimalistisches Design und eine hohe optische Leistung auszeichnet. Es eignet sich für Akzentbeleuchtungsanwendungen und bietet die Möglichkeit, verschiedene Farbtemperaturen und Abstrahlwinkel mit CRI98 zu kombinieren.

Proyector colgante para instalación empotrada sin bordes, caracterizado por un diseño mínimo y un alto rendimiento óptico. Se presta para aplicaciones de iluminación de acento, dando la oportunidad de combinar varias temperaturas de color y ángulos de haz, con CRI85.

CE IP20 made in Italy

Supply current
500mA (V, 2,9V)


Power
2W

Series wiring


CRI
85

2-Step MacAdam

Dimensions




Photometric diagrams



CCT/CRI/Flux

| | |
|-------|--------|
| 2700K | 128 lm |
| 3000K | 133 lm |
| 4200K | 154 lm |

Code construction




Note: Made-to-measure cable available on request.

Accessories

ZQC001 ZQC001B
White Black

Plasterboard recessing frame



AL7022

24VDC/500mA constant current converter

Drivers 500mA

on/off

AL1074 (1..7) IP20 30 mm

AL1077 (1..6) IP20 40 mm

AL1084 (1..11) IP20 S.P. 55 mm

dimmmable

AL4010 (1..12) IP20 PUSH 0/1..10V 72 mm

ALD450 (1..7) IP20 DALI 2 PUSH 36 mm

AL4151 (2..14) IP20 DALI 2 72 mm

AL4153 (1..14) IP20 PUSH IGBT-TRIAC 56 mm