

LOLLO X230

Adjustable downlights

design Lapo Grassellini




The Lollo range of orientable, recessed fixtures offers high performance in extremely compact dimensions. Its highly innovative dissipative system and off-axis inclination offer a 45° orientation of the full beam out from the ceiling, in a fixture of minimal yet sophisticated design.

La gamma di incassi orientabili Lollo offre alte prestazioni in dimensioni estremamente compatte. Lo studio di un sistema di dissipazione estremamente innovativo, unita all'inclinazione fuori dall'asse dell'apparecchio, consente un'orientabilità di 45° che mantiene tutto il flusso luminoso fuori dal filo del soffitto, in un apparecchio dal design minimale e sofisticato.

La gamme d'encastables orientables Lollo offre des prestations élevées dans des dimensions extrêmement compactes. L'étude d'un système de dissipation extrêmement innovant, unie à l'inclinaison hors de l'axe de l'appareil, permet une orientabilité de 45° qui maintient tout le flux lumineux hors du niveau du plafond, dans un appareil au design minimaliste et sophistiqué.

Die Produktreihe von ausrichtbaren Einbauleuchten Lollo bietet beste Leistungen in extrem kompakten Größen. Die Forschung eines extrem innovativen Ableitungssystem, verbunden mit der Neigung außerhalb der Achse des Gerätes, ermöglicht eine Ausrichtung von 45°, die den gesamten Lichtstrom weg von dem Draht der Decke hält, in einem Gerät von minimalistischen und anspruchsvollen Design.

IP20 made in Italy



115x340mm


Supply current
500mA (V_i 3x36V)

Power
3x20W


CRI
85-93

2-Step MacAdam

Dimensions




Photometric diagrams



CCT/CRI/Flux (3x)

	CRI85	CRI93
2700K	1830lm	1700lm
3000K	2000lm	1830lm
4000K	2100lm	1950lm

Code construction



Note: The finishing refers to the outer ring of the luminaire only, the inner part of the optical compartment is always black.

Drivers 500mA

on/off

AL1084 (1) IP20 S.P. ⌀ 55 mm

dimmmable

AL4010 (1) IP20 PUSH 0/1..10V ⌀ 72 mm

ALB451 (1) IP20 DALI 2 PUSH ⌀ 46 mm

AL4151 (1) IP20 DALI 2 ⌀ 72 mm

AL4153 (1) IP20 PUSH IGBT-TRIAC ⌀ 56 mm

Note: Each fixture needs 3 drivers.