FLEXA
LIGHTING

NORA TRIMLESS UGR

Trimless & adjustable downlight

IP44 made in Italy

design Roberto Mantovani



An extremely compact adjustable trimless recessed luminaire with a minimalist design, combining high lumen output with precise, clean optics for applications ranging from accent to general lighting. The recessed optic ensures a high level of visual comfort.

Incasso trimless orientabile dalle dimensioni estremamente compatte e dal design minimale, caratterizzato dalla capacità di unire elevati flussi luminosi ad ottiche precise e pulite, per illuminazioni che spaziano dall'accento all'illuminazione generale. L'ottica arretrata garantisce un alto comfort visivo.

Un luminaire encastré trimless orientable aux dimensions extrêmement compactes et au design minimaliste, capable d'associer des flux lumineux élevés à des optiques précises et nettes, pour des applications allant de l'éclairage d'accentuation à l'éclairage général. L'optique en retrait garantit un haut niveau de confort visuel.

Eine äußerst kompakte, schwenkbare rahmenlose Einbauleuchte mit minimalistischem Design, die hohe Lichtströme mit präzisen und sauberen Optiken verbindet und sich für Anwendungen von der Akzent- bis zur Allgemeinbeleuchtung eignet. Die zurückversetzte Optik gewährleistet einen hohen visuellen Komfort.

Una luminaria empotrable trimless orientable de dimensiones extremadamente compactas y diseño minimalista, capaz de combinar elevados flujos luminosos con ópticas precisas y limpias, para aplicaciones que abarcan desde la iluminación de acento hasta la iluminación general. La óptica retranqueada garantiza un elevado confort visual.

Supply current
500mA (V_f 18V)


Power
10W

Series wiring


CRI
85 (2200K)
93 (2700K-3000K-4000K)

2-Step MacAdam

Dimensions



Photometric diagrams



CCT/CRI/Flux

2200K	**810 lm**
2700K	**840 lm**
3000K	**930 lm**
4000K	**960 lm**


Code construction

NTTU X X X


- **S** 36° / **M** 46°
- **1** 2200K / **2** 2700K / **3** 3000K / **4** 4000K
- **1** White / **5** Black / **6** Bronze

Accessories

ZQSU001 White
ZQSU001B Black
Plasterboard recessing frame



TOOL75
Trimless tool



LNTTU01
Low luminance louver



SNTTU01
Milky screen



Note
The filter and the screen must be ordered together with the lighting fixture.

Drivers 500mA

on/off
AL1074 (1) IP20 30 mm
AL1077 (1) IP20 40 mm
AL1084 (1..2) IP20 S.P. 55 mm

dimmable
AL4010 (1..2) IP20 PUSH 0/1..10V 72 mm
ALMINI50 (1) IP20 DALI 2 PUSH 30 mm
AL4151 (1..2) IP20 DALI 2 PUSH 72 mm
AL4153 (1..2) IP20 PUSH IGBT-TRIAC 56 mm