


ZERO Q10

Trimless downlights

design Jude Allen



Trimless recessed downlight characterised by a minimalist design and high lighting performance. It offers the possibility of combining colour temperatures and beam angles, with CRI85 or CRI93, and can be equipped with the anti-glare filter accessory to ensure the best visual comfort of the installation.

Incasso trimless ad ottica arretrata caratterizzato da un design minimale e da alte prestazioni luminose. Offre la possibilità di combinare temperature colore ed aperture di fascio, con CRI85 o CRI93 ed è equipaggiabile con l'accessorio filtro antiabbagliamento, per assicurare il miglior comfort visivo dell'installazione.

Spot encastré sans garniture, caractérisé par un design minimaliste et des performances d'éclairage élevées. Il offre la possibilité de combiner les températures de couleur et les angles de rayonnement, avec IRC85 ou IRC93, et peut être équipé de l'accessoire filtre anti-éblouissement pour garantir le meilleur confort visuel de l'installation.

Einbaudownlight ohne Rahmen, das sich durch ein minimalistisches Design und eine hohe Lichtleistung auszeichnet. Es bietet die Möglichkeit, Farbtemperaturen und Ausstrahlungswinkel mit CRI85 oder CRI93 zu kombinieren, und kann mit dem Zubehör Blendschutzfilter ausgestattet werden, um den besten visuellen Komfort der Installation zu gewährleisten.

IP44 made in Italy

Supply current

500mA (V_f 18V)

Power

10W


Series wiring

CRI


85-93 (2700K-3000K-4000K only)

2-Step MacAdam

Dimensions



Photometric diagrams




CCT/CRI/Flux

CCT	CRI85	CRI93
2200K	810lm	
2700K	890lm	840lm
3000K	1000lm	930lm
4000K	1040lm	960lm

Code construction

ZQ1 X X X X




Accessories

ZQC005 ZQC005B

White Black

Plasterboard recessing frame



LZQ101

Low luminance louver



SZQ101

Milky screen



Note: The filter and the screen must be ordered together with the lighting fixture.

AL7022

24VDC/500mA constant current converter

Drivers 500mA

on/off

AL1074 (1) IP20 ⌀30 mm

AL1077 (1) IP20 ⌀40 mm

AL1084 (1..2) IP20 S.P. ⌀55 mm

dimmmable

AL4010 (1..2) IP20 PUSH 0/1..10V ⌀72 mm

ALD450 (1) IP20 DALI 2 PUSH ⌀36 mm

AL4151 (1..2) IP20 DALI 2 ⌀72 mm

AL4153 (1..2) IP20 PUSH IGBT-TRIAC ⌀56 mm