


ZERO Q RGB

RGB trimless downlight

design Roberto Mantovani



Revolutionary trimless, recessed fixtures, with diameters starting from just 30mm and an extremely clean and simple fixing system, offer innovative compositional possibilities and recessed optics for high viewing comfort. Available in multiple beam angles and ideal for applications ranging from the accenting of display elements and architectural details to general lighting.

Incassi trimless rivoluzionari: con diametri che partono da soli 30mm ed un sistema di fissaggio alla cassaforma estremamente semplice e pulito, offrono inedite possibilità compositive, con ottiche arretrate per un elevato comfort visivo. Disponibili in molteplici aperture di fascio si prestano ad applicazioni che spaziano dall'accento di elementi espositivi o di dettagli architettonici all'illuminazione generale.

Des encastrables trimless révolutionnaires: avec des diamètres qui partent de 30 mm seulement et un système de fixation au coffrage extrêmement simple et propre, ils offrent des possibilités de composition inédites, avec des optiques en retrait pour un confort visuel élevé. Disponibles dans des ouvertures de faisceau multiples, ils se prêtent à des applications qui vont de la mise en valeur d'éléments d'exposition ou de détails architectoniques à l'éclairage général.

Revolutionäre trimless Einbauten: mit Durchmesser von nur 30 mm und einem äußerst einfachen und sauberen Befestigungssystem an der Schalung, bieten sie neue Möglichkeiten der Komposition, mit Einbauoptiken für einen verbesserten visuellen Komfort. Erhältlich in verschiedenen Strahlenbündeln eignen sie sich für Anwendungen, die von Lichtakzenten für Ausstellungselemente oder architektonische Details bis zur Allgemeinbeleuchtung reichen.

CE  IP44 made in Italy

Supply current


3x350mA

Power

3x1W


Series wiring

Dimensions



Photometric diagrams

F003



Code construction

ZC2 X 2 9


1 5
White Black

Accessories

ZQC002 ZQC002B

White Black

Plasterboard recessing frame



Drivers/Controllers

Push control

C03010 (2..9 fixtures) IP20 PUSH

Radio control system

C03010 (2..9 fixtures) IP20

C01062 Radio receiver - Ricevitore radio

AL2031 Driver 24VDC

C01063 Radio remote control - Telecomando

Note: All codes are required for correct installation of the radio control system.